

FD-2014 Protex Front Loading Deposit Safe

Decription

- Protex B-rated depository drop safes are designed for ease of use and are a great choice for convenient stores, hotels/motels, churches, gas stations/car wash, restaurants and more.
- The safe is equipped with laser cut 1/2" steel plate door, spring loaded re-locker and chrome plated heavy-duty steel locking bolts as well as an anti-drill lock plate.
- The SecuRam electronic lock is a standard feature for the drop safe which gives it a very convenient and fast operation as well as easy programming and a wrong-try penalty lockout mode to prevent from manipulation of the lock.



Specifications

- Exterior Dimensions: 355mm (W) x 510mm (H) x 381mm (D)
- Interior Dimensions: 350mm (W) x 229mm (H) x 280mm (D)
- Door Thickness: 63mm (12mm solid steel plate)
- Volume: 22 litre
- Weight: 41 kg

Overview

- Solid steel construction, fully welded body construction.
- Convenient large drop door with anti-fish design.
- Securam electronic digital lock.
- 1/4" thick carburized hard-plate to resist drilling.
- Spring loaded active re-locker.
- Door is constructed from anti-pry 12mm thick solid steel plate.
- 4 pre-drilled mounting holes on bottom of safe (12mm dia).
- 3 chrome plated heavy duty bolts (25mm dia.).
- Bolt detent spring will throw the bolts when door is shut.
- Heavy-duty vault hinges.
- Quality powder coat finish.